

**Indoor/Outdoor Wet  
Location Enclosure**

**Auto Shut Down &  
Reset Overload  
Protection**

**Reliable Power Source  
for LED Lighting  
Applications**


**Magnetic  
Dimmer Ready**

**36 Month Limited  
Warranty**



**Multi Output  
Series**

Height: 14.25 inches  
Depth: 4.437 inches  
Width: 8.437 inches  
Weight: 40 lbs




All Drivers available with 120VAC or 277VAC Input options and 12VDC or 24VDC Output options.

Approvals      UL1310 Listed, Class2 Power Supplies,  
UL1310, UL48 Recognized Sign Accessories

**Multi Output:** C2240 Series - 12/24 VDC Outputs

**Single Output  
Series**

Height: 11.25 inches  
Depth: 3.25 inches  
Width: 3.37 inches  
Weight: 7.0 lbs



**Single Output:** 961 Series - 24VDC  
601 Series - 12VDC  
481 Series - 24VDC  
361 Series - 12VDC



**DIMMABLE LED DRIVERS**  
**UL LISTED/RECOGNIZED CLASS 2**

MODEL	INPUT VAC	INPUT AMPS	HZ	OUTPUT VAC	OUTPUT INFO
<b>12 VOLT OUTPUT</b>					
CC2240-12DCR	120	2.2	50 / 60	12	4 / 60 WATTS
CC2240-12DCR-277	277	0.87	50 / 60	12	4 / 60 WATTS
601-12DCR	120	0.81	50 / 60	12	1 / 60 WATTS
603-12DCR-277	277	0.38	50 / 60	12	1 / 60 WATTS
361-12DCR	120	0.58	50 / 60	12	1 / 36 WATTS
363-12DCR-277	277	0.24	50 / 60	12	1 / 36 WATTS
<b>24 VOLT OUTPUT</b>					
CC2240-24DCR	120	2.5	50 / 60	24	3 / 96 WATTS
CC2240-24DCR-277	277	1.04	50 / 60	24	3 / 96 WATTS
961-24DCR	120	1.12	50 / 60	24	1 / 96 WATTS
963-24DCR-277	277	0.5	50 / 60	24	1 / 96 WATTS
481-24DCR	120	0.63	50 / 60	24	1 / 48 WATTS
483-24DCR-277	277	0.28	50 / 60	24	1 / 48 WATTS
120 VAC AND 277 VAC INPUT OPTIONS 12 VDC AND 24 VDC OUTPUT OPTIONS					

**Ordering Options**

MODEL NUMBER		NUMBER OF UNITS
<input type="text"/>	Multiple Circuit	<input type="text"/>
<input type="text"/>	Single Circuit	<input type="text"/>
<input type="text"/>	Single Circuit	<input type="text"/>
		Total Units <input type="text"/>